

## Avide LED Flood Light Slim 50W CW 6400K

<b>Product code:</b>	ABSFLCW-50W
<b>Brand link:</b>	<a href="http://avidelighting.com/qr/ABSFLCW-50W">avidelighting.com/qr/ABSFLCW-50W</a>
<b>ID:</b>	AB-190518
<b>Company name:</b>	Bramcke Hungary Kft.
<b>Company address:</b>	Kisatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-09-04

Page: 1/3

### SPECIFICATIONS

EAN code:	5999097913865
Warranty:	3year(s)
Working temperature:	-20 - +40 °C
Packaging:	1/b 5/c 225/p
Certifications:	CE

### TECHNICAL DETAILS

Wattage:	50W
Voltage:	85-265V
Beam angle:	120°
Dimmability:	No
Lumen output:	3 000lm
Color temperature:	6 400K
Lifetime:	25 000h
Energy class:	G
Type of LED:	COB
Driver:	
CRI:	>80
IP standard:	IP65

### BOX PICTURE



**Avide LED Flood Light Slim 50W CW 6400K**

**Product code:** ABSFLCW-50W  
**Brand link:** [avidelighting.com/qr/ABSFLCW-50W](https://avidelighting.com/qr/ABSFLCW-50W)  
**ID:** AB-190518  
**Company name:** Bramcke Hungary Kft.  
**Company address:** Kishatár utca 17., 4031 Debrecen



Date of issue: 2024-09-04

Page: 2/3

**PRODUCT SIZE**

Width: 235mm  
 Height: 285mm  
 Depth: 55mm

**CARDBOARD BOX**

EAN: 5999097913865  
 Packaging: 1/b 5/c 225/p  
 Dimensions: 248mm x 65mm x 310mm  
 Net weight: 1 548.8g  
 Gross weight: 1 600g

**CARTON**

EAN: 5999097913872  
 Packaging: 1/b 5/c 225/p  
 Dimensions: 345mm x 260mm x 330mm  
 Net weight: 7.744kg  
 Gross weight: 8kg


**PALLET EXAMPLE**

Height:  
 Width: 120cm (std Euro pallet)  
 Mepth: 80cm (std Euro pallet)  
 Cartons per pallet: 45carton/pallet  
 Cartons per row:  
 Net weight: 348.48kg  
 Gross weight: 360kg

**PRODUCT PICTURE**



**PRODUCT OUTLINE**



## Avide LED Flood Light Slim 50W CW 6400K

<b>Product code:</b>	ABSFLCW-50W
<b>Brand link:</b>	<a href="https://avidelighting.com/qr/ABSFLCW-50W">avidelighting.com/qr/ABSFLCW-50W</a>
<b>ID:</b>	AB-190518
<b>Company name:</b>	Bramcke Hungary Kft.
<b>Company address:</b>	Kishatár utca 17., 4031 Debrecen

QR code:



Date of issue: 2024-09-04

Page: 3/3

### PRODUCT DESCRIPTION

The battery-operated Avide COB LED floodlights enable portable, mobile use. Brightness is adjustable in two stages. They can provide the same brightness as traditional halogen floodlights but with much lower power consumption; thus when operated from a battery, they can ensure a longer operating time. The battery of the floodlight can be fully charged in 3 hours and with one full charge it can operate for up to 5 hours. COB (chip-on-board) represents one of the most recent LED technologies, focusing the emitted light much better and thus providing better lighting at a longer distance. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

The LED floodlights are sold with a 30 cm long cable end and the plug is not included in the package! The product may only be installed by a professional! Any operation with the power on carries the hazard of an electric shock.

The Avide COB Floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10W / 20W / 30W / 50W / 80W / 100W / 150W power output versions. The "SLIM" design is also available in neutral white (NW) / cold white (CW) color temperatures and a 10W / 20W / 30W / 50W power output.